



# Castor ML-DGa

Die cast   DOB   30000h   100°





On/Off



cutout size

Φ 100mm	
Φ 121*38mm	IP54
10W	
1000lm	
100lm/W	
PF0.9	

On/Off

Φ 150mm	
Φ 172*38mm	IP54
20W	
2000lm	
100lm/W	
PF0.9	

On/Off

Φ 200mm	
Φ 221*38mm	IP54
30W	
3000lm	
100lm/W	
PF0.9	

# Specifikacija za Castor ML-DGa Downlight



## Karakteristike:

1. Kućište liveno pod pritiskom u tri različite dimenzije
2. Ultra tanak: 38mm
3. 100lm/w
4. Dug životni vijek 30,000Hrs, 3 godine garancija
5. PF0.9
6. Klasa I.
7. Sa kablom dužine 20cm cable, bez redne stezaljke



Model	Napon/V	Snaga	Lumen	CCT (K)	CRI	PF	Lm/W	Dimenzije D*H/mm	Instalacioni otvor (mm)	IP	Dimabilan	Ugao osvjetljenja	Životni vijek/H
Castor ML-DGa	220-240	10W	1000	3000/4000/6500	>80	>0.9	100lm/W	Φ121*38	Φ100	IP54	Ne	100°	30000
Castor ML-DGa	220-240	20W	2000	3000/4000/6500	>80	>0.9	100lm/W	Φ172*38	Φ150	IP54	Ne	100°	30000
Castor ML-DGa	220-240	30W	3000	3000/4000/6500	>80	>0.9	100lm/W	Φ221*38	Φ200	IP54	Ne	100°	30000