














| No. | Fotografija | Proizvod | Opis | | | | | | | |
|-----|---|-------------------|---|--|--|--|--|--|--|--|
| 1 |  | EName | LED Floodlight (black color) 10w | | | | | | | |
| | | LED floodlight | 800lm IP65 | | | | | | | |
| | | Buyer item no. | 1) Aluminum die-casting housing with tempered glass with frame | | | | | | | |
| | | EL-LPFL-10X01 | 2) SMD 2835 LED | | | | | | | |
| | | Supplier item no. | 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.5 7) Life time: 25000hours 8) Nominal Beam angle in dgrees: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP | | | | | | | |
| 2 |  | EName | LED Floodlight (black color) 30w | | | | | | | |
| | | LED floodlight | 2400lm IP65 | | | | | | | |
| | | Buyer item no. | 1) Aluminum die-casting housing with tempered glass with frame | | | | | | | |
| | | EL-LPFL-30X01 | 2) SMD 2835 LED | | | | | | | |
| | | Supplier item no. | 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgrees: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP | | | | | | | |


| | | | | | | | | | | | | | | | | |
|-------------------|---|--|-------|----------------|----------------|----------------|-------------------|--|--|--|--|--|--|--|--|--|
| 3 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-50X01</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-50X01 | Supplier item no. | <p>LED Floodlight (black color) 50w 4000lm IP65 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-50X01 | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 4 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-100X01</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-100X01 | Supplier item no. | <p>LED Floodlight (black color) 100w 8000lm IP65 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-100X01 | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 5 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-10X02</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-10X02 | Supplier item no. | <p>LED Floodlight (white color) 10w 800lm IP65 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.5 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-10X02 | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 6 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-30X02</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-30X02 | Supplier item no. | <p>LED Floodlight (white color) 30w 2400lm IP65 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-30X02 | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | |
|-------------------|---|--|-------|----------------|----------------|----------------|-------------------|---|--|--|--|--|--|--|--|--|
| 7 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-50X02</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-50X02 | Supplier item no. | <p>LED Floodlight (white color) 50w 4000lm IP65 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-50X02 | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 8 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-100X02</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-100X02 | Supplier item no. | <p>LED Floodlight (white color) 100w 8000lm IP65 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-100X02 | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 9 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-10X01-</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-10X01- | Supplier item no. | <p>LED Floodlight (black color) 10w with PIR sensor 800lm IP54 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.5 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-10X01- | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 10 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-30X01-</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-30X01- | Supplier item no. | <p>LED Floodlight (black color) 30w with PIR sensor 2400lm IP54 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP</p> | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-30X01- | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | |
|-------------------|---|--|-------|----------------|----------------|----------------|-------------------|--|--|--|--|--|--|--|--|--|
| 11 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-20X01-</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-20X01- | Supplier item no. | <p>LED Floodlight (black color) 20w with PIR sensor 1600lm IP54</p> <ol style="list-style-type: none"> 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.5 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-20X01- | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 12 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPEL-50X01-</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPEL-50X01- | Supplier item no. | <p>LED Floodlight (black color) 50w with PIR sensor 4000lm IP54</p> <ol style="list-style-type: none"> 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.9 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPEL-50X01- | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 13 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-10X02-</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-10X02- | Supplier item no. | <p>LED Floodlight (white color) 10w with PIR sensor 800lm IP54</p> <ol style="list-style-type: none"> 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.5 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-10X02- | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |
| 14 |  | <table border="1"> <tr><td>EName</td></tr> <tr><td>LED floodlight</td></tr> <tr><td>Buyer item no.</td></tr> <tr><td>EL-LPFL-20X02-</td></tr> <tr><td>Supplier item no.</td></tr> </table> | EName | LED floodlight | Buyer item no. | EL-LPFL-20X02- | Supplier item no. | <p>LED Floodlight (white color) 20w with PIR sensor 1600lm IP54</p> <ol style="list-style-type: none"> 1) Aluminum die-casting housing with tempered glass with frame 2) SMD 2835 LED 3) Voltage: AC 220-240V,50Hz 4) CCT: 6500K 5) Measured color rendering(Ra): >80 6) PF: >0.5 7) Life time: 25000hours 8) Nominal Beam angle in dgree: 120° 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) 10) warranty 2 years 11) package: color box, 2 in 1 12) certificate : CE ROHS ERP | | | | | | | | |
| EName | | | | | | | | | | | | | | | | |
| LED floodlight | | | | | | | | | | | | | | | | |
| Buyer item no. | | | | | | | | | | | | | | | | |
| EL-LPFL-20X02- | | | | | | | | | | | | | | | | |
| Supplier item no. | | | | | | | | | | | | | | | | |



| | | | | | | | | | | |
|----|---|-------------------|--|--|--|--|--|--|--|--|
| 15 |  | EName | LED Floodlight (white color) 30w | | | | | | | |
| | | LED floodlight | with PIR sensor 2400lm IP54 | | | | | | | |
| | | Buyer item no. | 1) Aluminum die-casting housing with tempered glass with frame | | | | | | | |
| | | Supplier item no. | 2) SMD 2835 LED | | | | | | | |
| | | | 3) Voltage: AC 220-240V,50Hz | | | | | | | |
| | | | 4) CCT: 6500K | | | | | | | |
| | | | 5) Measured color rendering(Ra): >80 | | | | | | | |
| | | | 6) PF: >0.9 | | | | | | | |
| | | | 7) Life time: 25000hours | | | | | | | |
| | | | 8) Nominal Beam angle in dgree: 120° | | | | | | | |
| | | | 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) | | | | | | | |
| | | | 10) warranty 2 years | | | | | | | |
| | | | 11) package: color box, 2 in 1 | | | | | | | |
| | | | 12) certificate : CE ROHS ERP | | | | | | | |

| | | | | | | | | | | |
|----|--|-------------------|--|--|--|--|--|--|--|--|
| 16 |  | EName | LED Floodlight (white color) 50w | | | | | | | |
| | | LED floodlight | with PIR sensor 4000lm IP54 | | | | | | | |
| | | Buyer item no. | 1) Aluminum die-casting housing with tempered glass with frame | | | | | | | |
| | | Supplier item no. | 2) SMD 2835 LED | | | | | | | |
| | | | 3) Voltage: AC 220-240V,50Hz | | | | | | | |
| | | | 4) CCT: 6500K | | | | | | | |
| | | | 5) Measured color rendering(Ra): >80 | | | | | | | |
| | | | 6) PF: >0.9 | | | | | | | |
| | | | 7) Life time: 25000hours | | | | | | | |
| | | | 8) Nominal Beam angle in dgree: 120° | | | | | | | |
| | | | 9) With 0.15m H05RN-F3G1.0mm2 cable (black color) | | | | | | | |
| | | | 10) warranty 2 years | | | | | | | |
| | | | 11) package: color box, 2 in 1 | | | | | | | |
| | | | 12) certificate : CE ROHS ERP | | | | | | | |

