



Basic Accessories



Available with stainless steel triangle hook for hanging installation.



Connection box help install easily



IP65 LED Water Proof

Fixture

Application

Offices, stores, hospitals, schools, lobbies and supermarkets etc.

Technical Parameter

1. Voltage: 220V-240V
2. Illuminant: SMD 2835
3. Power Factor: 0.9

Product Information

1. Polycarbonate body, high hardness, smooth surface, not easy to distort, excellent heat dissipation, and complete control of the light source of light failure
2. Source:
 - A Using 2835 chip, low power, high luminous efficiency, low light decline, good color rendering performance.
 - B low heat, long life
 - C low carbon, energy saving, environmental friendly, mercury-free
3. Class II



1230*200*308mm

| | LG06A-06-18 | LG06A-12-36 | LG06A-15-48 |
|------------------|-------------------|-------------------|-------------------|
| Wattage | 18W | 36W | 48W |
| LED | SMD2835 | SMD2835 | SMD2835 |
| LED quantity | | | 252 |
| Lumen | 1500lm or 1800lm | 3000lm or 3600lm | 4000lm or 4800lm |
| Light Efficiency | 83lm/w or 100lm/w | 83lm/w or 100lm/w | 83lm/w or 100lm/w |
| CRI | >80 | >80 | >80 |
| Length | 590 | 1180 | 1480 |
| Width | 86 | 86 | 86 |
| Height | 66 | 66 | 72 |
| A1 | 380±10 | 970±10 | 890±10 |
| Q'ty/ctn | 12pcs | 8pcs | 8pcs |
| Packaging size | 640*294*308mm | 1230*200*308mm | 1530*200*332mm |

Input Voltage: 220-240V 50/60Hz PF: 0.90 CCT: 2700-6500K

WORKING TEMPERATURE CONDITIONS: -15°C - 40°C

IP65 LED Water Proof

Fixture

